

Unication

The Only Submersible Voice Pager

DESIGNED FOR FIREFIGHTERS

IP67 Rating

Waterproof Dustproof

Available in Low Band, VHF, UHF

Scan Modes

Free, Silent,
Normal, Priority

2 Year Warranty
With additional 3 years

Standard Features

Bluetooth Voice Memo

Voice Storage

AAA Batteries

Up to 64 Channels

Programmable Music

& Voice Alerts



Unication Makes a \$20 Donation From the Sale of Each Red G1 to the National Fallen Firefighters Foundation

The G1 is rich with standard features including 16 minutes of stored voice and 11 minutes of voice memo. This enables you to record your own personal messages for on-the-scene reminders, notes, etc! The included Bluetooth allows you to pair your G1 with other devices. There are seven different backlight color options that allow you to assign colors to different channels.

This device is a software-defined pager that allows for updates with the latest features. Don't miss out on the most rugged voice pager on the market! With included features and units in stock, we have your back while you serve your community!

Available in Red, Yellow, Black, and Pink.

Get Connected: www.Facebook.com/UnicationUsalnc Visit our Website: www.UnicationUSA.com

817–346–2886/ UnicationUSA.com/ Sales@Unication.com 1901 East Lamar Blvd/ Arlington, Texas 76006



G1 STANDARD FEATURES

G1 GSM FEATURES

Signaling Options: 2 Tone, 5/6 Tone

CDCSS(DPL), CTCSS(PL)

AAA Batteries: Rechargeable or Alkaline

16 Minutes voice storage 11 Minutes voice memo

7 Backlight colors

64 Channels

Rejects cellphone interferences

Message Lock

Duty On/Off feature

Auto On/Off feature

Bluetooth (compatible with most phones and headsets)

Scan Modes:

Normal (Probability Scan)

Free, Priority, Silent, Monitor, Selective Standard 2 years warranty (5 years optional) Includes all standard features Receive text messages Provide automatic or manual acknowledgements to received or unreceived messages

ADDITIONAL INFORMATION

Weighs 200g Dimensions (mm) 100.5 x 65.2 x 26.45 Charger comes standard Charger detects alkaline and rechargeable batteries Charger Amplifier (optional): Extensive input, output control Submersible to 3 ft. for up to 30 minutes. Heavy duty belt clip Temperature range: −10°C ~ +50°C Special rubberdized housing

TECHNICAL SPECIFICATIONS

RF Perf/Band	Low	VHF	UHF	the fire fire
Sensitivity/Alerting (uV/m)	3.5	2	3	
Sensitivity/12dB SINAD (uV/M)	9	8	9	
Frequency Stability (ppm)	+-10	+-3	+-3	
Adjacent Channel Selectivity	70/65dB 25/12.5kHz (VHF)			
Spurious	>70dB			
Image Rejection	>70dB			
Audio Output Linear	>300mw			
Audio Distortion	<3%			
SPL Output (12")	96dB			
Speech Output (12:)	94dB			
Dust/Water Proof Level	IP67			
UL	Class I, Div. II			
FCC	FCC Part 15			
MIL-STD	810E, Procedures 1 for Driving Rain			
Channel Spacing	Narrowband or Wideband			
Frequency Band	Low B	and	VHF	UHF
Frequency Range (MHz)	33-39		137-	153 450-470
	43-49	•	148-	164 465-485
				495-512
	100000			



Reliable. Rugged. Built to Last.